

Pike Industries, Inc.
Franklin County
Farmington, Maine
A-765-71-D-R (SM)

) **Departmental**
) **Findings of Fact and Order**
) **Air Emission License**

After review of the air emissions license renewal application, staff investigation reports and other documents in the applicant's file in the Bureau of Air Quality, pursuant to 38 M.R.S.A., Section 344 and Section 590, the Department finds the following facts:

I. REGISTRATION

A. Introduction

Pike Industries, Inc. of Lewiston, Maine has applied to renew their Air Emission License permitting the operation of emission sources associated with their Farmington, Maine hot mix asphalt facility (**P703**).

B. Emission Equipment

Pike Industries, Inc. is authorized to operate the following equipment:

Asphalt Batch Plant

<u>Equipment</u>	<u>Production Rate (tons/yr)</u>	<u>Maximum Capacity (MMBtu/hr)</u>	<u>Date of Manufacture</u>	<u>Control Devices</u>
Rotary Kiln (P703)	300	96.8	1999	Baghouse

AC Hot Oil Heater

<u>Equipment</u>	<u>Maximum Capacity (MMBtu/hr)</u>	<u>Fuel Type, % Sulfur</u>	<u>Maximum Firing Rate (gallon/hour)</u>
Hot Oil Heater (P703)	1.5	#2 fuel oil, 0.4%S #4 fuel oil, 0.7%S Spec. Waste oil, 0.7%S	10.7

Pike Industries, Inc.
Franklin County
Farmington, Maine
A-765-71-D-R (SM)

)
)
)
2

**Departmental
Findings of Fact and Order
Air Emission License**

Electrical Generation Equipment

<u>Equipment</u>	<u>Power Output (kW)</u>	<u>Fuel Type, % Sulfur</u>	<u>Maximum Firing Rate (gal/hr)</u>	<u>Stack #</u>
Genset 3412C	760	#2 Fuel Oil, 0.05%	52.3	1
Sand Screen Unit	100	Diesel fuel, 0.05%	52.3	1

C. Application Classification

The application for Pike Industries, Inc. does not include the licensing of increased emissions or the installation of new or modified equipment. Therefore, the license is considered to be a renewal of current licensed emission units only. With the fuel limit on the Rotary Kiln (P703), Hot Oil Heater, Genset 3412C and the Sand Screen Genset the facility is licensed below the major source thresholds and is considered a synthetic minor.

II. BEST PRACTICAL TREATMENT (BPT)

A. Introduction

In order to receive a license the applicant must control emissions from each unit to a level considered by the Department to represent Best Practical Treatment (BPT), as defined in Chapter 100 of the Department regulations. Separate control requirement categories exist for new and existing equipment as well as for those sources located in designated non-attainment areas.

BPT for existing emissions equipment means that method which controls or reduces emissions to the lowest possible level considering:

- the existing state of technology;
- the effectiveness of available alternatives for reducing emissions from the source being considered; and
- the economic feasibility for the type of establishment involved.

B. Asphalt Drum Plant

Pike Industries, Inc. operates a portable continuous mix Drum type hot mix asphalt plant, designated P703, for the production of asphalt at their Farmington, Maine asphalt facility. The asphalt plant has a maximum designed heat input capacity of 96.8 MMBtu/hr and a maximum design process rate of 300 tons per hour.

Pike Industries, Inc.
Franklin County
Farmington, Maine
A-765-71-D-R (SM)

)
)
)
3

Departmental
Findings of Fact and Order
Air Emission License

Pike Industries, Inc. was previously licensed to fire no greater than 1,380,000 gallons per year (gal/yr) of a combination of #2 fuel oil with a sulfur content of no greater than 0.4% sulfur by weight, and specification waste oil with a sulfur content of no greater than 0.4% sulfur by weight, in P907, based on a twelve-month rolling total. Pike Industries, Inc. has requested a reduction in the fuel restriction, in conjunction with a reduction in the fuel restriction for the diesel units, to reduce the total annual emissions of criteria pollutants for the facility to levels below the Department's Chapter 137 applicability thresholds. Pike Industries, Inc. has requested that the annual fuel restriction for fuel oil fired in asphalt plant P703 be reduced to firing no greater than 450,000 gal/yr of a combination of #2 fuel oil with a sulfur content of no greater than 0.4% sulfur by weight, #4 fuel oil with a sulfur content of no greater than 0.7% sulfur by weight and specification waste oil with a sulfur content of no greater than 0.7% sulfur by weight, in P703, on a calendar year basis.

In order to demonstrate compliance with fuel restrictions, Pike Industries, Inc. shall maintain a record of fuel use for the asphalt plant, which shall include fuel purchase receipts indicating the quantity and supplier certification indicating sulfur content of the purchased fuel. The fuel record shall be maintained on a calendar year basis.

Only waste oil meeting the criteria "specification" waste oil (as defined in the "Waste Oil Management Rules") may be fired in the asphalt plant. Pike Industries, Inc. shall keep the results of a representative waste oil test on site. If the equipment or operations that produce the on-site waste oil change, then a new representative sample shall be tested. The Department may also request additional testing in the future, if deemed necessary.

The asphalt plant was manufactured in 1999 and is therefore subject to EPA New Source Performance Standards (NSPS) Subpart I for Hot Mix Asphalt Facilities. As a requirement of NSPS Subpart I, Pike Industries, Inc. shall perform a performance test in accordance with 40 CFR 60.8 and 40 CFR 60.93. Pike contracted ROJAC Air Testing Services, Inc., of Bloomfield, Connecticut, to conduct the required compliance testing in October, 1999. A copy of the compliance testing report showing compliance with the facility's air emission license was submitted to the Department by Pike and is on file.

The asphalt plant is subject to both the NSPS and the BPT Particulate matter (PM) emissions standard, however, the BPT standard is more stringent, therefore, only the more stringent PM emission standard of 0.03 gr/dscf shall be included in this license.

Pike Industries, Inc.
Franklin County
Farmington, Maine
A-765-71-D-R (SM)

)
)
)
4

Departmental
Findings of Fact and Order
Air Emission License

To meet requirements of BPT, the asphalt plant vents to a baghouse. The performance of the baghouse shall be constantly monitored by either of the following at all times the batch plant is in operation:

1. PM Detector – when the detector signals excessive PM concentrations in the exhaust stream, Pike Industries, Inc. shall take corrective action within 24 hours, or immediately if opacity exceeds 20% based on a 6-minute block average basis.
2. Personnel with an EPA Method 9 visible emissions certification within the past 6 months – when the opacity exceeds 20%, the hot mix asphalt batch plant is operating with insufficient control and Pike Industries, Inc. shall take corrective action immediately.

Pike Industries, Inc. shall establish a system of maintenance, inspection and repair for the asphalt plant baghouse, which shall allow for periodic inspection of the system. Pike Industries, Inc. shall document compliance by means of a maintenance, inspection and repair log in which Pike Industries, Inc. shall record the date all bag failures and all routine maintenance as well as all inspection dates and findings.

A summary of the BPT analysis for the Asphalt Plant is as follows.

1. BPT for PM is emissions not to exceed 0.03 gr/dscf. PM₁₀ emission limits are based on PM limits.
2. For the use of #2 fuel oil, BPT is a sulfur content not to exceed 0.4% sulfur by weight, for the use of specification waste oil, BPT is a sulfur content not to exceed 0.7% sulfur by weight and for the use of #4 fuel oil, BPT is a sulfur content not to exceed 0.7% sulfur by weight.
3. NO_x, CO and VOC emission limits are based upon AP-42 data dated 12/00.
4. Visible Emissions for the Asphalt Plant baghouse is limited to no greater than 20% opacity on a 6-minute block average, except for no more than two 6-minute block averages in a continuous 3-hour period

Pike Industries, Inc. may process up to 10,000 cubic yards per year of soil contaminated by gasoline or #2 fuel oil without prior approval from the Department. This limit may be exceeded with written authorization from the Department. The plant owner or operator shall notify the commissioner at least 24 hours prior to processing the contaminated soil and specify the contaminating fuel and quantity, origin of the soil and fuel and the disposition of the contaminated soil.

Pike Industries, Inc. may process up to 5,000 cubic yards per year of soil contaminated with virgin oil as defined by the Bureau of Air Quality without prior approval from the Bureau of Air Quality. Virgin oil processing shall be done at a mixture of no greater than 30% contaminated soil to 70% clean aggregate mix. Processing of virgin oil contaminated soils may require a solid waste processing facility license under MEDEP Chapter 409. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management.

Virgin Oil Definition:

Virgin oil means any petroleum derived oil, including petroleum fuels, unused motor oils, hydraulic fluids, lubrication oils and other industrial oils, that are not characterized as waste oil.

Pike Industries, Inc. shall not process soils which are classified as hazardous waste or which have unknown contaminants.

When processing contaminated soils, Pike Industries, Inc. shall maintain records which specify the quantity and type of contaminant in the soil as well as the origin and characterization of the contaminated soil. In addition, when processing contaminated soil, Pike Industries, Inc. shall maintain records of processing temperature, asphalt feed rates and dryer throughput on an hourly basis. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management.

C. AC Hot Oil Heater

Pike Industries, Inc. operates an AC hot oil heater, designated P703-1, for heating oil used as a heating medium for the asphalt storage silo. The hot oil heater has a maximum designed heat input capacity of 1.5 MMBtu/hr firing #2 fuel oil.

- D.** Pike Industries, Inc. shall include the fuel consumed in the AC Hot Oil Heater as part of the asphalt plant fuel record, also the total fuel consumed in the heater shall be included under the licensed asphalt plant fuel restriction of 450,000 gallons per year.

A summary of the BPT analysis for the AC hot oil heater is as follows.

1. BPT for PM for the AC hot oil heater is 0.12 lb/MMBtu. PM₁₀ emission limits are based on PM limits.
2. BPT sulfur content for the use of #2 fuel oil fired in the AC hot oil heater is no greater than 0.5% sulfur by weight and for the use of #4 fuel oil and specification waste oil, BPT is a sulfur content not to exceed 0.7% sulfur by weight.

3. SO₂, NO_x, CO and VOC emission rates are based on AP-42 data dated 9/98 for oil fired boilers firing #2 fuel oil (0.5% Sulfur).
4. Visible emissions from the AC hot oil heater shall not exceed 20% on a 6-minute block average.

E. Genset 3412C

Pike Industries, Inc. operates a 760 kW diesel genset, designated Genset 3412C, primarily as power sources for the asphalt batch plant. Pike Industries, Inc. was previously licensed to fire no greater than 94,000 gallons per year (gal/yr) of diesel fuel oil, with a sulfur content of no greater than 0.05% sulfur by weight based on a twelve-month rolling total. Pike Industries, Inc. has requested a reduction in the fuel restriction, in conjunction with a reduction in the fuel restriction for the asphalt plant, to reduce the total annual emissions of criteria pollutants for the facility to levels below the Department's Chapter 137 applicability thresholds. Pike Industries, Inc. has requested that the annual fuel restriction for diesel fuel fired in the diesel units be reduced to firing no greater than 59,000 gal/yr of diesel fuel with a sulfur content of no greater than 0.05% sulfur by weight, on a calendar year basis.

To demonstrate compliance with the fuel restrictions, Pike Industries, Inc. shall maintain a record of fuel oil purchases, which shall include receipts indicating the amount of fuel delivered and certification from the supplier indicating the sulfur content of the purchased fuel. The fuel record shall be maintained on a monthly as well as on a calendar year basis.

A summary of the BPT analysis for Genset 3412C is as follows

1. BPT for SO₂ is the use of diesel fuel with a sulfur content of 0.05% by weight.
2. BPT for PM for the AC hot oil heater is 0.12 lb/MMBtu. PM₁₀ emission limits are based on PM limits.
3. NO_x, CO and VOC emission limits are based on AP-42 data dated 10/96 for large stationary diesel engines.
4. Visible emissions from the diesel unit shall not exceed 30% opacity on a 6-minute block average except, for no more than two 6-minute block averages in a 3-hour period.

F. Sand Screen Genset

Pike Industries, Inc. operates a sand screen unit at their Farmington, Maine hot mix asphalt facility. The sand screen unit is powered by a diesel generator unit designated the Sand Screen Genset.

BPT for the Sand Screen Genset shall be a total annual fuel use limit of 20,000 gallons of diesel fuel oil at 0.05% sulfur by weight on a calendar year basis. To demonstrate compliance with the fuel restrictions, Pike Industries, Inc. shall maintain a record of fuel oil purchases, which shall include receipts indicating the amount of fuel delivered and certification from the supplier indicating the sulfur content of the purchased fuel. The fuel record shall be maintained on a calendar year basis.

A summary of the BPT analysis for the Sand Screen Genset is as follows

1. BPT for SO₂ is the use of diesel fuel with a sulfur content of 0.05% by weight.
2. BPT for PM for the Sand Screen Genset is 0.12 lb/MMBtu. PM₁₀ emission limits are based on PM limits.
3. NO_x, CO and VOC emission limits are based on AP-42 data dated 10/96 for industrial diesel engines of less than 600 horsepower.
4. Visible emissions from the diesel unit shall not exceed 30% opacity on a 6-minute block average except, for no more than two 6-minute block averages in a 3-hour period.

G. Fugitive Emissions

Visible emissions from potential sources of fugitive particulate matter emissions, including material stockpiles and unpaved roadways, shall not exceed an opacity of 20 percent, except for no more than 5-minutes in any 1-hour period. Compliance shall be determined by an aggregate of the individual 15-second opacity observations which exceed 20 percent in any 1-hour. Stock Piles and Roadways.

H. Annual Emission Restrictions

- Total fuel use in the asphalt plant, including the AC hot oil heater, shall not exceed 450,000 gal/year of a combination of #2 fuel oil with a sulfur content of no greater than 0.4% sulfur by weight, specification waste oil with a sulfur content of no greater than 0.7% sulfur by weight and #4 fuel oil with a sulfur content no greater than 0.7% sulfur by weight, on a calendar year basis.
- Total fuel use in Genset 3412C shall not exceed 59,000 gal/year of diesel fuel oil with a sulfur content of no greater than 0.05% sulfur by weight.
- Total fuel use in Sand Screen Genset shall not exceed 20,000 gal/year of diesel fuel oil with a sulfur content of no greater than 0.05% sulfur by weight.

Pike Industries, Inc.
Franklin County
Farmington, Maine
A-765-71-D-R (SM)

)
)
)
8

Departmental
Findings of Fact and Order
Air Emission License

Pike Industries, Inc. shall be assessed fees based on the following annual emissions:

Pollutant	Tons/Year			
	Asphalt Drum Plant	Genset 3412C	San Screen Genset	<u>Total</u>
PM	1.6	0.5	0.2	2.3
PM ₁₀	1.6	0.5	0.2	2.2
SO ₂	22.2	0.2	0.1	22.5
NO _x	5.4	13.2	6.2	24.8
CO	12.7	3.5	1.3	17.5
VOC	4.3	0.4	0.5	5.2

III.AMBIENT AIR QUALITY ANALYSIS

According to the Maine Regulations Chapter 115, the level of air quality analyses required for a minor source shall be determined on a case-by case basis. Based on the information available in the file, and the similarity to existing sources, Maine Ambient Air Quality Standards (MAAQS) will not be violated by this source. Based on the total facility emissions, Pike Industries, Inc. is below the emissions level required for modeling and monitoring.

ORDER

Based on the above Findings and subject to conditions listed below, the Department concludes that the emissions from this source:

- will receive Best Practical Treatment,
- will not violate applicable emission standards,
- will not violate applicable ambient air quality standards in conjunction with emissions from other sources.

The Department hereby grants Air Emission License A-765-71-D-R subject to the following conditions:

STANDARD CONDITIONS

- (1) Employees and authorized representatives of the Department shall be allowed access to the licensee's premises during business hours, or any time during which any emissions units are in operation, and at such other times as the Department deems necessary for the purpose of performing tests, collecting samples, conducting inspections, or examining and copying records relating to emissions (Title 38 MRSA §347-C).

- (2) The licensee shall acquire a new or amended air emission license prior to commencing construction of a modification, unless specifically provided for in Chapter 115.
- (3) Approval to construct shall become invalid if the source has not commenced construction within eighteen (18) months after receipt of such approval or if construction is discontinued for a period of eighteen (18) months or more. The Department may extend this time period upon a satisfactory showing that an extension is justified, but may condition such extension upon a review of either the control technology analysis or the ambient air quality standards analysis, or both.
- (4) The licensee shall establish and maintain a continuing program of best management practices for suppression of fugitive particulate matter during any period of construction, reconstruction, or operation which may result in fugitive dust, and shall submit a description of the program to the Department upon request.
- (5) The licensee shall pay the annual air emission license fee to the Department, calculated pursuant to Title 38 M.R.S.A. §353.
- (6) The license does not convey any property rights of any sort, or any exclusive privilege.
- (7) The licensee shall maintain and operate all emission units and air pollution systems required by the air emission license in a manner consistent with good air pollution control practice for minimizing emissions.
- (8) The licensee shall maintain sufficient records to accurately document compliance with emission standards and license conditions and shall maintain such records for a minimum of six (6) years. The records shall be submitted to the Department upon written request.
- (9) The licensee shall comply with all terms and conditions of the air emission license. The filing of an appeal by the licensee, the notification of planned changes or anticipated noncompliance by the licensee, or the filing of an application by the licensee for a renewal of a license or amendment shall not stay any condition of the license.
- (10) The licensee may not use as a defense in an enforcement action that the disruption, cessation, or reduction of licensed operations would have been necessary in order to maintain compliance with the conditions of the air emission license.

- (11) In accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department, the licensee shall:
- (i) perform stack testing to demonstrate compliance with the applicable emission standards under circumstances representative of the facility's normal process and operating conditions:
 - a. within sixty (60) calendar days of receipt of a notification to test from the Department or EPA, if visible emissions, equipment operating parameters, staff inspection, air monitoring or other cause indicate to the Department that equipment may be operating out of compliance with emission standards or license conditions; or
 - b. pursuant to any other requirement of this license to perform stack testing.
 - (ii) install or make provisions to install test ports that meet the criteria of 40 CFR Part 60, Appendix A, and test platforms, if necessary, and other accommodations necessary to allow emission testing; and
 - (iii) submit a written report to the Department within thirty (30) days from date of test completion.
- (12) If the results of a stack test performed under circumstances representative of the facility's normal process and operating conditions indicate emissions in excess of the applicable standards, then:
- (i) within thirty (30) days following receipt of such test results, the licensee shall re-test the non-complying emission source under circumstances representative of the facility's normal process and operating conditions and in accordance with the Department's air emission compliance test protocol and 40 CFR Part 60 or other method approved or required by the Department; and
 - (ii) the days of violation shall be presumed to include the date of stack test and each and every day of operation thereafter until compliance is demonstrated under normal and representative process and operating conditions, except to the extent that the facility can prove to the satisfaction of the Department that there were intervening days during which no violation occurred or that the violation was not continuing in nature; and

- (iii) the licensee may, upon the approval of the Department following the successful demonstration of compliance at alternative load conditions, operate under such alternative load conditions on an interim basis prior to a demonstration of compliance under normal and representative process and operating conditions.
- (13) Notwithstanding any other provisions in the State Implementation Plan approved by the EPA or Section 114(a) of the CAA, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any statute, regulation, or Part 70 license requirement.
- (14) The licensee shall maintain records of malfunctions, failures, downtime, and any other similar change in operation of air pollution control systems or the emissions unit itself that would affect emission and that is not consistent with the terms and conditions of the air emission license. The licensee shall notify the Department within two (2) days or the next state working day, whichever is later, of such occasions where such changes result in an increase of emissions. The licensee shall report all excess emissions in the units of the applicable emission limitation.
- (15) Upon written request from the Department, the licensee shall establish and maintain such records, make such reports, install, use and maintain such monitoring equipment, sample such emissions (in accordance with such methods, at such locations, at such intervals, and in such a manner as the Department shall prescribe), and provide other information as the Department may reasonably require to determine the licensee's compliance status.

SPECIFIC CONDITIONS

- (16) Asphalt Plant
 - A. Total fuel use in the asphalt plant shall not exceed 450,000 gal/year of a combination of #2 fuel oil with a sulfur content of no greater than 0.4% sulfur by weight, #4 fuel oil with a sulfur content of no greater than 0.7% sulfur by weight and specification waste oil with a sulfur content of no greater than 0.7% sulfur by weight, on a calendar year basis. [MEDEP Chapter 115, BPT]
 - B. Pike Industries, Inc. shall maintain a record of fuel use for the asphalt plant, which shall include fuel purchase receipts indicating the quantity and supplier certification indicating sulfur content of the purchased fuel. The fuel record shall be maintained monthly basis as well as a calendar year basis. [MEDEP Chapter 115, BPT]

- C. Only waste oil meeting the criteria “specification” waste oil (as defined in the “Waste Oil Management Rules”) may be fired in the asphalt plant. [MEDEP Chapter 115, BPT]
- D. Pike Industries, Inc. shall keep the results of a representative waste oil test on site. If the equipment or operations that produce the on-site waste oil change, then a new representative sample shall be tested. The Department may also request additional testing in the future, if deemed necessary. [MEDEP Chapter 115, BPT]
- E. Emissions from the asphalt plant shall vent to a baghouse and all components of the asphalt batch plant shall be maintained so as to prevent particulate matter leaks. [MEDEP Chapter 115, BPT]
- F. Visible Emissions for the Asphalt Plant baghouse are limited to no greater than 20% opacity on a 6-minute block average, except for no more than two 6-minute block averages in a continuous 3-hour period. [MEDEP Chapter 101]
- G. The performance of the baghouse shall be constantly monitored by either of the following at all times the batch plant is in operation:
 - 1. PM Detector – when the detector signals excessive PM concentrations in the exhaust stream, Pike Industries, Inc. shall take corrective action within 24 hours, or immediately if opacity exceeds 20% based on a 6-minute block average basis.
 - 2. Personnel with an EPA Method 9 visible emissions certification within the past 6 months – when the opacity exceeds 20%, the hot mix asphalt batch plant is operating with insufficient control and Pike Industries, Inc. shall take corrective action immediately.[MEDEP Chapter 115, BPT]
- H. Pike Industries, Inc. shall establish a system of maintenance, inspection and repair for the asphalt plant baghouse, which shall allow for periodic inspection of the system. Pike Industries, Inc. shall document compliance by means of a maintenance, inspection and repair log in which Pike Industries, Inc. shall record the date of all bag failures and all routine maintenance as well as all inspection dates, findings and corrective actions. [MEDEP Chapter 115, BPT]

- I. Emissions from the asphalt plant shall not exceed the following:

Equipment		PM	PM₁₀	SO₂	NO_x	CO	VOC
Asphalt	Grs/dscf	0.03	-	-	-	-	-
Batch Plant	lb/hr	4.8	4.8	68.2	16.5	39.0	13.2

[MEDEP Chapter 115, BPT]

- J. Fugitive particulate matter emissions from the asphalt plant operation shall be controlled so as to prevent visible emissions in excess of 10% opacity except for one 6-minute block average in any continuous 1-hour period. [MEDEP Chapter 101]

- K. Pike Industries, Inc. may process up to 10,000 cubic yards per year of soil contaminated by gasoline or #2 fuel oil without prior approval from the Department. This limit may be exceeded with written authorization from the Department. The plant owner or operator shall notify the commissioner at least 24 hours prior to processing the contaminated soil and specify the contaminating fuel and quantity, origin of the soil and fuel and the disposition of the contaminated soil. [MEDEP Chapter 115, BPT]

- L. Pike Industries, Inc. may process up to 5,000 cubic yards per year of soil contaminated with virgin oil as defined by the Bureau of Air Quality without prior approval from the Bureau of Air Quality. Virgin oil processing shall be done at a mixture of no greater than 30% contaminated soil to 70% clean aggregate mix. Processing of virgin oil contaminated soils may require a solid waste processing facility license under MEDEP Chapter 409. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management. [MEDEP Chapter 115, BPT]

- M. Pike Industries, Inc. shall not process soils which are classified as hazardous waste or which have unknown contaminants. [MEDEP Chapter 115, BPT]

- N. When processing contaminated soils, Pike Industries, Inc. shall maintain records which specify the quantity and type of contaminant in the soil as well as the origin and characterization of the contaminated soil. In addition, when processing contaminated soil, Pike Industries, Inc. shall maintain records of processing temperature, asphalt feed rates and dryer throughput on an hourly basis. The material shall be handled in accordance with the requirements of the Bureau of Remediation and Waste Management. [MEDEP Chapter 115, BPT]

- O. Pike Industries, Inc. shall notify the Bureau of Air Quality regional inspector at least 7 days prior to processing soil contaminated with anything other than #2 fuel oil, gasoline or virgin oil. [MEDEP Chapter 115, BPT]

(17) AC Hot Oil Heater

A. Pike Industries, Inc. shall include the fuel consumed in the AC Hot Oil Heater (P703) as part of the asphalt plant fuel record, also the total fuel consumed in the heater shall be included under the currently licensed asphalt batch plant fuel restriction of 450,000 gallons per year. [MEDEP Chapter 115, BPT]

B. Emissions shall not exceed the following:

Equipment		PM	PM ₁₀	SO ₂	NO _x	CO	VOC
Hot Oil Heater	lb/hr	0.2	0.2	0.6	0.2	0.05	0.006

[MEDEP Chapter 115, BPT]

C. Visible emissions from the Hot Oil Heater shall not exceed 20% on a 6-minute block average. [MEDEP Chapter 101]

(18) Genset 3412C

A. Total fuel use for Genset 3412C shall not exceed 59,000 gal/year of diesel fuel with a maximum sulfur content of 0.05% by weight on a calendar year basis.

B. Compliance with the above fuel restriction shall be based on fuel receipts from the supplier showing the quantity of fuel delivered and supplier certification indicating sulfur content of the purchased fuel. The fuel record shall be maintained monthly basis as well as a calendar year basis. [MEDEP Chapter 115, BPT]

C. Emissions from Genset 3412C shall be limited to the following:

Equipment		PM	PM ₁₀	SO ₂	NO _x	CO	VOC
Genset 3412C	lb/MMBtu	0.12	-	-	-	-	-
	lb/hr	0.9	0.9	0.4	23.7	6.3	0.7

[MEDEP Chapter 103]

D. Visible emissions from Genset 3412C shall not exceed 30% opacity on a 6-minute block average, except for no more than 2 six-minute block averages in a continuous 3-hour period. [MEDEP Chapter 101]

(19) Sand Screen Genset

A. Total fuel use for the Sand Screen Genset shall not exceed 20,000 gal/year of diesel fuel with a maximum sulfur content of 0.05% by weight on calendar year basis.

B. Compliance with the above fuel restriction shall be based on fuel receipts from the supplier showing the quantity of fuel delivered and the percent sulfur of the fuel. The fuel record shall be maintained monthly basis as well as a calendar year basis. [MEDEP Chapter 115, BPT]

C. Emissions from the Sand Screen Genset shall be limited to the following

Equipment		PM	PM₁₀	SO₂	NO_x	CO	VOC
	lb/MMBtu	0.12	-	-	-	-	-
Sand Screen Genset	lb/hr	0.1	0.1	0.04	3.1	0.7	0.3

[MEDEP Chapter 103]

D. Visible emissions from the Sand Screen Genset shall not exceed 30% opacity on a 6-minute block average, except for no more than 2 six-minute block averages in a continuous 3-hour period. [MEDEP Chapter 101]

(20) Fugitive Emissions

Visible emissions from potential sources of fugitive particulate matter emissions, including material stockpiles and unpaved roadways, shall not exceed an opacity of 20%, except for no more than 5-minutes in any 1-hour period. Compliance shall be determined by an aggregate of the individual 15-second opacity observations which exceed 20% in any 1-hour. [MEDEP Chapter 101]

(21) Equipment Relocation [MEDEP Chapter 115, BPT]

A. Pike Industries, Inc. shall notify the Bureau of Air Quality, by a written notification at least 48 hours prior to relocation of any equipment carried on this license. Written notice may be sent by mail, facsimile (fax), or e-mail. Notification sent by mail shall be sent to the address below or to a Department Regional Office:

Attn: Relocation Notice
Maine DEP
Bureau of Air Quality
17 State House Station
Augusta, ME 04333-0017

Equipment relocation notification can also be done on-line with e-notice at www.maine.gov/dep/air/compliance/forms/relocation.

The notification shall include the address of the equipment's new location, an identification of the equipment and the license number pertaining to the relocated equipment.

Pike Industries, Inc.
Franklin County
Farmington, Maine
A-765-71-D-R (SM)

)
)
)
16

Departmental
Findings of Fact and Order
Air Emission License

- B. Written notification shall also be made to the municipality where the equipment will be relocated, except in the case of an unorganized territory where notification will be made to the respective county commissioners.
- (22) Pike Industries, Inc. shall keep a copy of this Order on site, and have the operator(s) be familiar with the terms of this Order. [MEDEP Chapter 115]
- (23) Pike Industries, Inc. shall notify the Department within 48 hours and submit a report to the Department on a quarterly basis if a malfunction or breakdown in any component causes a violation of any emission standard (38 MRSA §605-C).
- (24) Pike Industries, Inc. shall pay the annual air emission license fee within 30 days of June 30 of each year. Pursuant to 38 MRSA 353-A, failure to pay this annual fee in the stated timeframe is sufficient grounds for the revocation of the license under 38 MRSA 341-D, Subsection 3.

DONE AND DATED IN AUGUSTA, MAINE THIS DAY OF 2006.

DEPARTMENT OF ENVIRONMENTAL PROTECTION

BY: _____
DAVID P. LITTELL, COMMISSIONER

PLEASE NOTE ATTACHED SHEET FOR GUIDANCE ON APPEAL PROCEDURES

The term of this Order shall be for five (5) years from the signature above.

Date of initial receipt of application: **May 17, 2004**

Date of application acceptance: **May 26, 2004**

Date filed with the Board of Environmental Protection: _____

This Order prepared by, Peter G. Carleton, Bureau of Air Quality